VARIARE







Qty outer carton

10

Dimensions carton L x W x H

20 x 8 x 18 cm

Housing **RAL colour** Fixture type Module Driver Lumen output CCT CRI **Beam angles** Adapter Rotatable Tiltable **Expected Lifetime** Photobiological safety **Power factor** UGR **Colour consistency** Warranty

Aluminium, die cast 9004 (Black), 9003 (White) 3-phase track light America Delux LED Powergear® Ultimate adapter with build-in LED driver 900lm 3000K >90Ra 8º - 30º (adjustable beam angle) Powergear® 3-phase ultimate adapter included 350º 90º >40.000h (L70/B30) RG1 unlimited > 0.9 < 19 3 SDCM 3 years warranty on LED module and driver



Net Weight

625 grams





LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
America Delux LED	900Lm	18W	50	930	>90Ra						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

²) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light