





Ø 97

100

Housing

RAL colour Fixture type Module Driver Lumen output ССТ CRI **Beam angles** Expected Lifetime Photobiological safety **Power factor Colour consistency** Warranty

Aluminium, die cast 9004 (Black), 9003 (White), 9004/9003 (Black/White), 9004/1036 (Black/Gold) Surface mounted Dim-to-Warm LED module Osram TRIAC dimmable driver 900lm DTW 3000K-1800K >90Ra 40º >30.000h (L70/B30) RG1 unlimited > 0.9 3 SDCM 5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton			
595 grams	13 x 15 x 13 cm	20			

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Nuvola Round DTW	900Lm	7W	74	1800K-3000K	>90Ra						
						-					

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

²) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light